

YUIMA MUNICIPAL WATER DISTRICT METER / BACKFLOW INSTALLATION CHARGES

for parcels within the Improvement District see IDA sheet

Yuima Capacity Charges effective 01/01/2022. SDCWA System Capacity Charge Amounts effective 01/01/2022

METER SIZE	5/8 x 3/4"	1"	1 1/2"	2"	3"	4"
OPERATING GPM RANGE	(30 GPM)	(3-50 GPM)	(5-100 GPM)	(5-160 GPM)	(5-350 GPM)	(5-650 GPM)
ACREAGE REQUIREMENTS <small>(meter sizes are restricted to 6 gpm/ac per resolution 117-14)</small>	Lot - 3 ac	3 to 8	8+ to 16	16+ to 20	20+ to 60	60+ to 100
<u>COST FOR A STANDARD METER:</u>						
Meter Installation Charge	3,900	4,100	4,800	5,500	T&M	T&M
Standard Double Check Valve *	195	210	390	475	1,400	1,950
YMWD - System Capacity Charge***	3,338	5,341	10,017	17,361	32,048	54,752
SDCWA - System Capacity Charge	5,328	8,525	15,984	27,706	51,149	87,379
SDCWA - Water Treatment Capacity Cg.	149	238	447	775	1,430	2,443
Total Deposit Required	\$12,910	\$18,414	\$31,638	\$51,817	\$86,027	\$146,524
<u>METER COSTS WHEN THE SERVICE IS IN A SUBDIVISION WITH EXISTING SERVICE OUTLET:</u>						
Meter Installation Charge	800	1,000	1,400	1,600	T&M	T&M
Standard Double Check Valve *	195	210	390	475	1,400	1,950
YMWD - System Capacity Charge***	3,338	5,341	10,017	17,361	32,048	54,752
SDCWA - Capacity Charge	5,328	8,525	15,984	27,706	51,149	87,379
SDCWA - Water Treatment Capacity Cg.	149	238	447	775	1,430	2,443
Total Deposit Required	\$9,810	\$15,314	\$28,238	\$47,917	\$86,027	\$146,524
<u>METER COSTS WHEN GROVE WILL BE WATERED BY USING A FERTILIZER INJECTION SYSTEM:</u>						
Meter Installation Charge	3,900	4,100	4,800	5,500	T&M	T&M
Reduced Pressure Backflow Device **	315	400	685	900	2,400	3,200
YMWD - System Capacity Charge***	3,338	5,341	10,017	17,361	32,048	54,752
SDCWA - Capacity Charge	5,328	8,525	15,984	27,706	51,149	87,379
SDCWA - Water Treatment Capacity Cg.	149	238	447	775	1,430	2,443
Total Deposit Required	\$13,030	\$18,604	\$31,933	\$52,242	\$87,027	\$147,774
PRESSURE REDUCING VALVE	- Actual Cost -					
The district requires the installation of a PRV when pressure exceeds 150 psi at meter. Maximum meter operating pressure is 150 psi.						

*Double Check Valve assembly Approved by University of Southern California's List of Approved Backflow Prevention Devices

**Backflow device = Reduced Pressure Device approved by University of Southern California's List of Approved Backflow Prevention Devices

*** plus an additional charge to be determined by a study at the time of application for mtrs. 3" & larger.

A \$1,500 deposit to conduct a study is required for all meters 3" and larger and all tract maps.

T&M minimum deposit based on contractor quote for the job.

The meter installation charge is calculated to cover the cost of a typical meter installation.

If the installation charges exceed the meter installation minimum deposit amount set out above (due to excess lateral, etc.) the customer will be billed for any balance due.

Maximum meter size allowed on parcel determined by parcel size. Resolution #117-14

Last Update: 01/01/2022